

Features

- Aluminum die-casting case
- High strength paint
- Alloy steel load cell
- 115*41 mm LCD/LED display
- Alloy steel shackle and hook
- Optional clevis hook or swivel hook (1-5t)
- Optional waterproof IP66
- Optional Mor 18650 lithium battery
- Infrared remote control

Specifications

Accuracy class	OIML $\text{\textcircled{III}}$
Tare range	100%F.S.
Zero range	4%F.S.
Safe overload	120%F.S.
Ultimate overload	400%F.S.
Overload warning	100%F.S.+9e
Battery	AA*3/lithium battery
Adaptor	DC5V1A
Temperature range	-10°C~40°C

Functions

- Zero/Tare
- Display hold
- Voltage display
- Overload warning
- Auto power off
- Unit switch
- Resolution switch

Weight and size

Model	Max. cap. kg	d kg		A mm	B mm	C mm	D mm	E mm	F mm	L mm	H mm
OCS-1-V	1000	0.5	2000	173	74	50	55	103	33	440	370
OCS-2-V	2000	1	2000	173	74	50	55	103	33	440	370
OCS-3-V	3000	1	3000	173	74	50	55	103	33	440	370
OCS-5-V	5000	2	2500	173	74	55	70	103	33	490	405
OCS-10-V	10000	5	2000	173	95	83	97	103	43	605	530

➤ Any difference, subject to the actual dimension.

